# HCR-36 CLEANER CLEANER FOR RIGID PVC, PVC-C AND ABS.





#### STORAGE CONDITIONS

At least 36 months, if stored in a well-closed packaging in a dry place at a temperature between  $+5^{\circ}$ C and  $+25^{\circ}$ C. Limited shelf life after opening.

#### PRODUCT DESCRIPTION

Cleaner for cleaning and degreasing rigid PVC, PVC-c and ABS pipes, sockets and fittings to be glued. To be used in combination with HCR-36.

# **FIELD OF APPLICATION**

For cleaning and degreasing rigid PVC, PVC-c and ABS pipes, sockets and fittings to be glued. Also suitable for removing adhesive residue and cleaning brushes and tools. Not suitable for diluting HCR-36.

## **APPLICATION**

**Coverage:** Indication of the number of connections per 1 L:

Ø	32	40	50	63	75	90	110	125	160	200	250
#	800	700	650	550	330	250	160	140	90	50	35

## **Directions for use:**

- 1. Apply cleaner to a clean, highly absorbent cloth.
- 2. Clean and degrease surfaces to be joined.
- 3. Remove condensation with a clean cloth and allow to dry thoroughly. Seal packaging carefully immediately after use.

**Points of attention:** Always use in combination with Griffon HCR-36.

# **TECHNICAL SPECIFICATIONS**

Chemical base: Mixture of solvents.

**Colour:** Transparent **Viscosity:** approx. 1 mPa.s. **Density:** approx. 1.3 g/cm<sup>3</sup> **Flash point:** K1 (<21°C)

Our advice is based on extensive research and practical experience. However, in view of the large variety of materials and the conditions under which our products are applied, we assume no responsibility for the results obtained and/or any damage caused by the use of the product. Nevertheless, our Service Department is always at your disposal for any advice needed.